

NORDIC T10407 LD TURBO PLUS EXTRA

Fully Synthetic Engine Oil

Product Description

A premium heavy-duty synthetic technology engine oil developed for fleets requiring the widest possible OEM approval coverage. Combines CK-4, CJ-4 and CI-4 compatibility with excellent soot handling, oxidation stability and after-treatment protection.

Applications

- Euro IV, Euro V and Euro VI trucks
- Modern SCR and DPF equipped fleets
- Mixed OEM fleets
- Long-haul transportation
- Off-road and industrial diesel equipment

⚠ Always check the vehicle owners manual for the correct oil specification before use.

Performance Benefits

- ✓ **Maximum Approval Coverage:** Suitable for highly diverse fleets.
- ✓ **After-Treatment Protection:** Low SAPS technology protects DPF and SCR systems.
- ✓ **Extended Drain Capability:** Supports modern long-drain maintenance programs.
- ✓ **Excellent Shear Stability:** Maintains viscosity under severe operating conditions.

Specifications

- | | | |
|------------|------------|-----------------|
| • ACEA E11 | • ACEA E9 | • API CI-4 Plus |
| • ACEA E6 | • API CK-4 | • API CI-4 |
| • ACEA E7 | • API CJ-4 | • API SN |
| • ACEA E8 | | |

Specifications

- AGCO Power
- Allison C4
- Caterpillar ECF-1a/2/3
- Cummins CES 20076 / 20081 / 20086 / 20092 / 20100
- Detroit Diesel DFS 93K215 / 93K218 / 93K222
- Deutz DQC IV-10 LA / 18 LA
- Ford WSS-M2C171-F1
- Iveco TLS E6 / E9
- JDQ-78X
- Mack EO-O Premium Plus
- Mack EOS-4.5
- MAN M3477 / 3575 / 3775
- MB 235.28
- MTU Category 2.1 / 3.1
- Renault RLD-3 / 4
- Scania LA
- Volvo VDS-4 / 4.5
- Voith Retarder Class B

Typical Properties

Property	Method	Value
Density @ 15°C	ASTM D4052	0.858 g/ml
Viscosity @ 40°C	ASTM D445	95.0 mm ² /s
Viscosity @ 100°C	ASTM D445	14.5 mm ² /s
Viscosity Index	ASTM D2270	158
TBN	ASTM D2896	10.2 mg KOH/g
CCS @ -25°C	ASTM D5293	6600 mPa·s
Pour Point	ASTM D6892	-33°C
Flash Point COC	ASTM D92	216°C

User Advice

- ⚠ Always Verify Vehicle Compatibility before use

Storage, Handling & Environmental Advice

- **Storage:** Store upright in a cool, dry place below 60°C. Avoid direct sunlight and freezing conditions.
- **Handling:** Avoid contamination with other fluids. Always reseal containers after use.
- **Environmental Precautions:** Dispose of used oil and packaging in accordance with local environmental regulations.

Health and Safety

- **NORDIC Oil** presents no significant risk to health or the environment when used properly. Refer to the Safety Data Sheet (SDS) for full safety, handling, and environmental information.

Refer to the latest Safety Data Sheet before use.